

Fast 03 1C

Anti-intrusion fogging security systems



PROFESSIONAL AT A COMPETITIVE PRICE

It is the ideal fogging system to protect small and medium areas like shops, homes, banks.

It is the entry level of the professional line, shoots up to 200 m³ of dense fog in 15 seconds.

It is equipped with a **single cylinder** and the shooting time can be set in seconds.

It is very fast and competitive.

UR Fog fogging systems are innovative in their technology and performances, in order to guarantee the most effective protection against thefts and they have different patents.

UR Fog fogging systems are certified after European regulation. Fog fluid is assessed as not dangerous for people and animals and does not leave residuals.



A unique serial bus to plug on the electronic board an add on card that allows to easily interface the machine with alarms and to control the fogging system even from remote. A standard protocol is available for all machines.



Fast electronic board



Powerful and fast fogging system, can cover up to **600 m³ in 15 seconds** (200 m³ recommended visibility).



Removable and disposable fog cylinder, very easy to change and with a very competitive price.



Vertical / horizontal recharge
Liquid quantity 400 ml



Easy to change cylinder



Battery pack



Thanks to the massive insulation UR FOG fogging systems have a very low power consumption and can shoot for a long time in absence of mains power; temperature is constantly stable.

Long lasting operation time without mains
The innovative thermal insulation of the heater allows UR Fog systems to work for a long period of time without mains power: from 1,5 h up to 3,5h!



UR Fog S.r.l.

Operation and delivery to: Via Toscana 38 - 10099 San Mauro T.se (Torino) - Italy | Legal Office: via Giacinto Collegno 11 - 10143 Torino - Italy

Phone +39 011 0133037

E-mail: info@urfog.com

C.F. / P. Iva 10724850010 - Reg. imprese TO - 1157030 - Numero Iscrizione Reg. AEE: IT19050000011412
Numero Iscrizione Reg. Pile Accumulatori IT19100P00005758 Cap. Soc. Euro 10.000 int. versati

Fast 03 1C

Anti-intrusion fogging security systems



GENERAL SPECIFICATIONS

Weight of the fog machine	about 10 KG
Weight with packaging	about 11 KG
Units on one pallet 100x120	36
Dimension of the machine	26,5 X23,0 XH34,5
Dimension of the packaging	32,0 X25,0 XH43,0
Colors	white
Working time without mains power	about 2 hours
Heat up time from cold	about 70 minutes
Vertical mounting	yes
Horizontal mounting	yes
Serial usb port for monitoring	yes
Nozzle tamper	yes
Serial bus for standard protocol	yes
Alarm kit	opzional

STANDARD

Complies with european CE	yes
Fog fluid is certified	yes
Meets european standard	yes

FOGGING SYSTEM

New heating system plus	yes
Coverage in a single shot (1,5 m visibility)	up to 600 m ³
Coverage in a single shot (recommended density)	up to 200 m ³
Max seconds of fog emission	15 sec
Max fog emitted with full fog tank	600 m ³
Number of cylinders	1
Fog tank capacity	1 x 400 ml
Shooting specification	programmable in seconds
Cylinder model	vertical / horizontal
Cylinder included	1

ELECTRICAL SPECIFICATIONS

Power supply	230 V or 110 V
Average power consumption	37 W
Battery pack	yes
Antirobbery kit	yes
Inputs wired arming and shooting	yes
Outputs wired	yes
Standard communication protocol	yes



UR Fog S.r.l.

Operation and delivery to: Via Toscana 38 - 10099 San Mauro T.se (Torino) - Italy | Legal Office: via Giacinto Collegno 11 - 10143 Torino - Italy

Phone +39 011 0133037

E-mail: info@urfog.com

C.F. / P. Iva 10724850010 - Reg. imprese TO - 1157030 - Numero Iscrizione Reg. AEE: IT19050000011412
Numero Iscrizione Reg. Pile Accumulatori IT19100P00005758 Cap. Soc. Euro 10.000 int. versati