

FAST
03 2C



Powerful and fast fogging system, can cover up to **600 m³ in 15 seconds** (200 m³ visibility less than 1 m).



200

GENERAL SPECIFICATIONS

Weight of the fog machine	about 11 KG
Weight with packaging	about 12 KG
Units on one pallet 100×120	36
Dimension of the machine	26,5 X23,0 XH34,5
Dimension of the packaging	32,0 X25,0 XH43,0
Colors	white
Working time without mains power	about 2 hours
Heating time from cold	about 50 minutes
Vertical mounting	yes
Horizontal mounting	yes
Usb port for monitoring	yes
Nozzle tamper	yes
Serial bus RS232	yes
Alarm kit	optional

STANDARD

Complies with european CE	yes
Fog fluid is certified	yes
Meets european standard	yes



FOGGING SYSTEM

New heating system "Layer"	yes
Coverage in a single shot (visibility more than 1,5 m)	up to 600 m ³
Coverage in a single shot (visibility less than 1 m)	up to 200 m ³
Max seconds of fog emission	15 sec
Max fog emitted with full fog tank	1600 m ³
Number of cylinders	2
Fog tank capacity	2 x 400 ml
Shooting specification	programmable in seconds
Cylinder model	vertical / horizontal
Cylinder included	2
Double fog tank patent	yes

ELECTRICAL SPECIFICATIONS

Mains power	230 V or 120 V
Average power consumption	37 W
Battery pack	yes
Antirobbery kit	yes
Inputs wired arming and shooting	yes
Outputs wired	yes
Standard communication protocol	yes